

Sanitary Vent HV125

Application

The HV125 vent from J.A. Plast is a sanitary vent. It is ideal as ventilation outlet from living quarters like kitchen, bathroom, tumbler and laundry room.

HV125 can also be used for mechanical ventilation.

Please refer to national standards.

Available as:

HV125 ISO – with insulated pipe
Ø 110 mm pipe fixed from factory

HV125 Solo – with non-insulated pipe
Ø 110 mm pipe fixed from factory

- For pitched roofs 15° – 45°
- Ø125/110/100 connection
- Can be manufactured for any profile

Design

The design of the HV125 vent diverts water around the vent and down the roof surface. The vent is supplied installed on a base plate shaped to fit the roof profile 100%. Easily installed with the rest of the roofing material and always following the roof pitch, the vent presents a nicely integrated solution.

Colour and Surface

Special coloured, glossy or structured with sand or granules the vents can be supplied with a 100% colour and surface match individually adjusted to each roofing material.

Materials

Vent and adapters: HIPS (High Impact Polystyrene).

Tubivent: PP (PolyPropylene).

Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Remove plastic bag before placing in sunlight.



Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, www.japlast.com.