

Clear Tile LP1000

Application

The LP1000 from J.A. Plast improves the amount of daylight entering unheated roof space. It is suitable for domestic, agricultural as well as industrial buildings.

The LP1000 can be used as single sheets spread over the roof or as a band of clear elements.

Please refer to national standards.

- · For pitched roofs
- · Quick and easy installation
- · For profiles with fixed batten spacing
- CE marked



Design

The LP1000 is shaped to match the specific roofing profile - corrugated sheets and steel roofing in particular. It is fixed like the rest of the roofing elements, making installation quick and easy and integration with the roofing profile complete. Remember to pre-drill holes with min. 4 mm oversize for installation.

LP1000 can be manufactured in a variety of sizes within max. 1190 x 1485 mm.

Colour and Surface

LP1000 is transparent.

Materials

The clear tile is manufactured from UV-resistant polycarbonate. A cover of protective foil prevents damage before installation. Available in 1 mm or 1.5 mm polycarbonate.

Polycarbonate has a supreme durability and UV resistance. It is crack resistant and impact-proof towards hailstorm and rough weather.

Handling

Keep in original packaging during transport.

Do not wrap and expose to heavy load during transport.

Do not store in sunlight. Remove protective foil before exposing to sunlight.

Roofing accessories supplied from J.A. Plast match roof profile, colour and surface 100%. The current product list and further information can be found on our homepage, www.japlast.com.